



3200W 3 Phase Input Industrial Power Supplies



Features	Benefits
• 400/440/480 VAC (Nominal) 3 Phase Delta or Wye	• Global Use
• Fully Regulated, Wide Range Adjustable Output	• Versatile Application
• Voltage and Current Programming	• Flexible Control Options
• -40°C (start up) to +70°C operation	• Suitable for Rugged Environments
• >92% Efficiency	• Easy System Cooling
• PMBus Communication	• Easier System Monitoring
• Built in ORing FET for parallel operation	• Suitable for N + 1 Redundancy

Specification				
Model	TPS3000-24		TPS3000-48	
Input Voltage (47-63Hz)	VAC	350 - 528VAC, Delta or Wye 3 phase		
Input Current	A	6A per phase max, steady state		
Inrush Current	A	<15A per phase (excluding initial spike charging EMI capacitors lasting <2mS)		
Power Factor Correction	-	0.93 typical		
Efficiency (1)	%	92.5%	92.5%	
Ripple & Noise (Pk-Pk) (max) (2)	mV	130mV	260mV	
Line Regulation	%	<0.25%		
Load Regulation	%	<0.5%		
Overcurrent Protection	-	Adjustable (70-105% of rated current)		
Overvoltage Protection	V	115% of setpoint (tracking)		
Thermal Protection	-	Internal thermostat. Automatic reset		
Hold Up Time	ms	>10mS at 80% of rated current, nominal input/output voltage		
Remote Sense	-	Compensates for a total of 1V cable drop		
Dropped Phase Signal	-	Open collector; off during normal operation, strobing during dropped phase state		
Remote On / Off	-	Selectable logic - enable or inhibit		
AC Fail Signal	-	Open Collector, ON when AC is above 340VAC and unit is enabled		
DC Good Signal	-	Open Collector, ON when output is above 85 to 95% of setpoint (tracking)		
Remote Adjust	-	0 - 5V adjusts output from V max to V min		
Parallel Connection	-	Single wire current share, up to 8 units. Built in ORing FET		
Standby Voltage	-	11.2V to 12.5V, 0.3A		
Operating Temperature	°C	-40°C to +70°C, see derating curve (20 min warm up needed for <-10°C)		
Storage Temperature	°C	-40°C to +85°C		
Temperature Coefficient	%/°C	0.02%/°C		
Humidity (non condensing)	%RH	10 - 90%RH		
Cooling	-	Internal variable speed fan		
Withstand Voltage	VAC	Input - Ground 2,000VAC, Input - Output 3,000VAC, Output - Ground 500VAC		
Isolation Resistance	MΩ	>100MΩ (25deg, 70%RH)		
Vibration	-	Designed to meet MIL-STD-810F, Method 514.5, Procedure I, Cat 1, 10		
Shock	-	Designed to meet MIL-STD-810F, Method 516.5, Procedure I, IV & VI		
Safety Agency Certifications	-	UL/CSA60950-1, EN60950-1, CE mark for LVD and RoHS2		
Voltage Dips	-	SEMI F47-0706		
Leakage Current	mA	<3mA		
Conducted Emissions	-	EN55022 Class A, FCC part 15 Class-A, (Class-B TBD)		
Immunity	-	EN61000-4-2, -3, -4, -5, -6, -8, -11		
Altitude	m	4000m		
Weight	kg	3.5		
Size (W x H x D)	mm	107 x 84.4 x 324 (excluding output busbars)		
Warranty	yrs	3		

Notes: (1) Typical, 75-100% at rated current (2) Consult Installation Manual for detailed specifications, test methods and application notes


Model Selector

Model	Nominal Voltage (V)	Adjust. ⁽⁴⁾ Range (V)	Rated Current (A)	Maximum ⁽³⁾ Current (A)	Rated Power (W)	Maximum ⁽³⁾ Power (W)
TPS3000-24	24	19.2 - 29	125	133.3	3000	3200
TPS3000-48	48	38.4 - 58	66.7	66.7	3200	3200


Notes: (3) Rated at nominal output voltage only.

(4) A minimum load of 0.5A is required to maintain regulation and ripple spec throughout the output voltage adjustment range.

Outline Drawing TPS3000 Series



Derating Curve TPS3000 Series





TDK-Lambda France SAS

3 Avenue du Canada
Parc Technopolis
Bâtiment Sigma
91940 les Ulis
France
Tel: +33 1 60 12 71 65
Fax: +33 1 60 12 71 66
france@fr.tdk-lambda.com
www.fr.tdk-lambda.com



Italy Sales Office

Via dei Lavoratori 128/130
20092 Cinisello Balsamo (MI)
Italy
Tel: +39 02 61 29 38 63
Fax: +39 02 61 29 09 00
info.italia@it.tdk-lambda.com
www.it.tdk-lambda.com



Netherlands

info@nl.tdk-lambda.com
www.nl.tdk-lambda.com



TDK-Lambda Germany GmbH

Karl-Bold-Strasse 40
77855 Achern
Germany
Tel: +49 7841 666 0
Fax: +49 7841 5000
info.germany@de.tdk-lambda.com
www.de.tdk-lambda.com



Austria Sales Office

Aredstrasse 22
2544 Leobersdorf
Austria
Tel: +43 2256 655 84
Fax: +43 2256 645 12
info@at.tdk-lambda.com
www.de.tdk-lambda.com



Switzerland Sales Office

Bahnhofstrasse 50
8305 Dietlikon
Switzerland
Tel: +41 44 850 53 53
Fax: +41 44 850 53 50
info@ch.tdk-lambda.com
www.de.tdk-lambda.com



Nordic Sales Office

Haderslevvej 36B
DK-6000 Kolding
Denmark
Tel: +45 2911 9556
info@dk.tdk-lambda.com



TDK-Lambda UK Ltd.

Kingsley Avenue
Ilfracombe
Devon EX34 8ES
United Kingdom
Tel: +44 (0) 12 71 85 66 66
Fax: +44 (0) 12 71 86 48 94
powersolutions@uk.tdk-lambda.com
www.uk.tdk-lambda.com



TDK-Lambda Ltd.

Kibbutz
Givat Hashlosha 48800
Israel
Tel: +9 723 902 4333
Fax: +9 723 902 4777
info@tdk-lambda.co.il
www.tdk-lambda.co.il



C.I.S.

Commercial Support:

Tel: +7 (495) 665 2627

Technical Support:

Tel: +7 (812) 658 0463
info@tdk-lambda.ru
www.tdk-lambda.ru

Local Distribution

we energize electronics!

RSG
an acal group company

RSG Electronic Components GmbH
Sprendlinger Landstr. 115
D-63069 Offenbach

Tel: +49.69.984047-0
Fax: +49.69.984047-77

Mailto:sales@rsg-electronic.de
http://www.rsg-electronic.de